

Activejet®

AJE-1600VA LCD

1600 VA uninterruptible power supply (UPS) unit.



Product colour	Black
Certification	CE
Input frequency	50/60 Hz
Manual	Yes
USB port	Yes
Ethernet LAN (RJ-45) ports	1
Housing material	Plastic
UPS topology	Line-Interactive
Input operation voltage (min)	162 V
Input operation voltage (max)	290 V
Surge protection	Yes
AC outlets quantity	6 AC outlet(s)
USB 2.0 ports quantity	1
Battery capacity	9 Ah
Battery voltage	12 V
Height	205 mm
Audible alarm(s)	Yes
Power protection features	Input fuse
Power protection features	Overload
Automatic battery test	Yes
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Output power	900 W

Response time	2 ms
Modem (RJ-11) ports	1
Power protection features	Over current
Power protection features	Over power
Power protection features	Over voltage
Power protection features	Under voltage
Depth	395 mm
Waveform	Sine
Power protection features	Battery discharge
Cold start	Yes
Compatibility	Linux, MAC, Unix, Windows 2000/2003/XP/Vista/2008/Windows7/8
Noise level	40 dB
Power protection features	Short circuit
Typical backup time at full load	5 min
Typical backup time at half load	20 min
Form factor	Mini Tower
Output operation voltage (min)	230 V
Automatic Voltage Regulation (AVR)	Yes
AC outlet types	Type E / F
Output frequency	50/60 Hz
Number of type F outputs	3
Number of output IEC jumpers	3
RS-232 ports	1
Number of battery cells	2
Battery recharge time	6 h
Built-in fan	Yes
Width	145 mm
Weight	9.7 kg
Cooling type	Active
Sustainability certificates	RoHS
Power plug	C14 coupler
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Output power capacity	1.6 kVA
Cables included	Power load cable, USB cable
Display type	LCD
Compliance certificates	RoHS
EAN	5901452158569