



# AJE-626VA LED

625 VA uninterruptible power supply (UPS) unit.



<b>Product colour</b>	Black
<b>Certification</b>	CE
<b>Input frequency</b>	50/60 Hz
<b>Manual</b>	Yes
<b>LED indicators</b>	Yes
<b>Housing material</b>	Plastic
<b>UPS topology</b>	Line-Interactive
<b>Input operation voltage (min)</b>	162 V
<b>Output operation voltage (max)</b>	230 V
<b>EMI/RFI noise filtering</b>	Yes
<b>Surge protection</b>	Yes
<b>Modem (RJ-11) ports</b>	2
<b>Battery voltage</b>	12 V
<b>Output power</b>	360 W
<b>Audible alarm(s)</b>	Yes
<b>AC outlets quantity</b>	2 AC outlet(s)
<b>Width</b>	100 mm
<b>Depth</b>	287 mm
<b>Height</b>	142 mm
<b>Power protection features</b>	Input fuse
<b>Power protection features</b>	Overload
<b>Number of type F outputs</b>	2
<b>Automatic battery test</b>	Yes

<b>Operating temperature (T-T)</b>	0 - 40 °C
<b>Operating relative humidity (H-H)</b>	0 - 90%
<b>Response time</b>	2 ms
<b>Power protection features</b>	Over current
<b>Power protection features</b>	Over power
<b>Power protection features</b>	Over voltage
<b>Power protection features</b>	Under voltage
<b>Waveform</b>	Sine
<b>Power protection features</b>	Battery discharge
<b>Battery capacity</b>	7 Ah
<b>Cold start</b>	Yes
<b>Compatibility</b>	Linux, MAC, Unix, Windows 2000/2003/XP/Vista/2008/Windows7/8
<b>Noise level</b>	40 dB
<b>Power protection features</b>	Short circuit
<b>Typical backup time at full load</b>	5 min
<b>Typical backup time at half load</b>	20 min
<b>Battery recharge time</b>	4 h
<b>Weight</b>	4.2 kg
<b>Form factor</b>	Mini Tower
<b>Automatic Voltage Regulation (AVR)</b>	Yes
<b>AC outlet types</b>	Type E / F
<b>LED indicators</b>	Activity
<b>LED indicators</b>	Fault
<b>LED indicators</b>	Power
<b>Output frequency</b>	50/60 Hz
<b>Sustainability certificates</b>	RoHS
<b>Audible alarm modes</b>	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
<b>Output power capacity</b>	0.625 kVA
<b>Input operation voltage (max)</b>	284 V
<b>EAN</b>	5901452123253