



AJE-626VA LED

625 VA uninterruptible power supply (UPS) unit.



Product colour	Black
Certification	CE
Input frequency	50/60 Hz
Manual	Yes
LED indicators	Yes
Housing material	Plastic
UPS topology	Line-Interactive
Input operation voltage (min)	162 V
Output operation voltage (max)	230 V
EMI/RFI noise filtering	Yes
Surge protection	Yes
Modem (RJ-11) ports	2
Battery voltage	12 V
Output power	360 W
Audible alarm(s)	Yes
AC outlets quantity	2 AC outlet(s)
Width	100 mm
Depth	287 mm
Height	142 mm
Power protection features	Input fuse
Power protection features	Overload
Number of type F outputs	2
Automatic battery test	Yes

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Response time	2 ms
Power protection features	Over current
Power protection features	Over power
Power protection features	Over voltage
Power protection features	Under voltage
Waveform	Sine
Power protection features	Battery discharge
Battery capacity	7 Ah
Cold start	Yes
Compatibility	Linux, MAC, Unix, Windows 2000/2003/XP/Vista/2008/Windows7/8
Noise level	40 dB
Power protection features	Short circuit
Typical backup time at full load	5 min
Typical backup time at half load	20 min
Battery recharge time	4 h
Weight	4.2 kg
Form factor	Mini Tower
Automatic Voltage Regulation (AVR)	Yes
AC outlet types	Type E / F
LED indicators	Activity
LED indicators	Fault
LED indicators	Power
Output frequency	50/60 Hz
Sustainability certificates	RoHS
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Output power capacity	0.625 kVA
Input operation voltage (max)	284 V
EAN	5901452123253