



AJE-EASY650 LCD

650 VA uninterruptible power supply (UPS) unit.



Product colour	Black
Certification	CE
Input frequency	50/60 Hz
Manual	Yes
Housing material	Plastic
UPS topology	Line-Interactive
EMI/RFI noise filtering	Yes
Surge protection	Yes
Battery voltage	12 V
Output power	360 W
Audible alarm(s)	Yes
AC outlet types	Type F
AC outlets quantity	2 AC outlet(s)
Width	100 mm
Depth	287 mm
Height	142 mm
Power protection features	Input fuse
Power protection features	Overload
Number of type F outputs	2
Battery capacity	7.2 Ah
Automatic battery test	Yes
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%

Response time	2 ms
Power protection features	Over power
Power protection features	Over voltage
Form factor	Tower
Waveform	Sine
Input operation voltage (max)	240 V
Power protection features	Battery discharge
Number of battery cells	1
Cold start	Yes
Compatibility	Linux, MAC, Unix, Windows 2000/2003/XP/Vista/2008/Windows7/8
Input operation voltage (min)	110 V
Output operation voltage (min)	85 V
Output operation voltage (max)	290 V
Noise level	40 dB
Power protection features	Short circuit
Typical backup time at full load	5 min
Typical backup time at half load	20 min
Battery recharge time	4 h
Weight	4.2 kg
RS-232 ports	1
Output power capacity	0.65 kVA
Display type	LCD
EAN	5901443015024